


PERC MONOCRYSTALLINE
108PM10


108_{cell}



Half Cut

Multi-BB

DARK SERIES



High Conversion Efficiency

High panel efficiency to guarantee high power output.



Self-Cleaning and Anti-Reflection Glass

Coating glass for self-cleaning reduces surface dust.




Outstanding Low Irradiation Glass

Outstanding panel performance even in weak light conditions.



Easy Installation



30 Years Performance Warranty



15 Years Product Warranty



IEC 61215, IEC 61730-1, IEC 61730-2
IEC 62804 PID (POTENTIAL INDUCED DEGRADATION)
IEC 61701 SALT MIST CORROSION
IEC 62716 AMMONIA CORROSION
ISO 9001:2015, ISO 14001:2015, ISO 45001:2018



SOMPO SIGORTA

DARK SERIES

108PM10

Peak Power (Pmax)
Module Efficiency (%)
Maximum Power Voltage (Vmp)
Maximum Power Current (Imp)
Open Circuit Voltage (Voc)
Short Circuit Current (Isc)
Power Tolerance
Maximum System Voltage
Operating Temperature
Protection Class
Maximum Series Fuse Rating

MECHANICAL SPECIFICATION

Cell Dimensions (mm)
Cells per Module (pcs)
Weight (kg)
Panel Dimensions (mm)
Max. Wind/Snow Load (Pa)
Junction Box
Junction Box Cable Length (mm)

TT395 108PM10	TT400 108PM10	TT405 108PM10	TT410 108PM10
395 Wp	400 Wp	405 Wp	410 Wp
20.23	20.48	20.74	21.00
30.90	31.10	31.30	31.50
12.79	12.86	12.94	13.02
36.90	37.10	37.40	37.60
13.62	13.70	13.77	13.85
0~+5W			
1500V DC			
-40 ~ +85°C			
Class II			
25A			
182x91			
108 (6x18)			
22.0			
1722x1134x30			
2400/5400			
IP68			
350-1600			

TEMPERATURE CHARACTERISTICS

PACKING CONFIGURATION



Container 40' GP

Temp. Coeff. of (Isc)	0.050%/°C
Temp. Coeff. of (Voc)	-0.270%/°C
Temp. Coeff. of (Pmax)	-0.350%/°C

Pieces per Pallet	36
Pieces per Container	936
Pallets per Container	26

PHYSICAL CHARACTERISTICS

ELECTRICAL CHARACTERISTICS



*The specifications are obtained under the standard test conditions: 1000W/m2 solar irradiance, 1.5 Air Mass and cell temperature of 25°C. Measurement uncertainty for all panels is 6%. The actual transactions will be subject to the contracts. These parameters are for reference only and it is not a part of the contracts. The technical specifications in this document may vary. For more information, refer to the "Installation Manual".

* For roof, facades and installations on similar surfaces, solar panels should be mounted over a fire-resistant covering suitable for this application, with adequate ventilation between the back of the solar panels and the mounting surface. Improper installations are hazardous and may spark a fire. Solar panels must not be mounted on structures and roofs which are made of not fire-resistant materials such as plastic layer, transparent plastic, PVC or similar materials without any fire-protection layer. Usage and installation not in accordance with the guidelines as outlined in the installation manual will terminate the warranty. Please refer to the installation manual and the warranty documents for further details.

* Please note that the color of PERC monocrystalline cells might vary slightly due to their natural structure. Consequently, there might be a color difference between the cells and between the cells and the backsheets.

* TommaTech® GmbH reserves the right to change the specification of products without prior notice.

Ver.2309.6